



DOOR OPENING: \_\_\_\_\_ W \_\_\_\_\_ H

QUANTITY: \_\_\_\_\_

COVER FABRIC: \_\_\_\_\_

COLOR: \_\_\_\_\_

OPTIONS (CHECK BOX IF APPLICABLE)

BLOWER POSITION:

- ☐ TOP LEFT
- ☐ TOP RIGHT
- ☐ SIDE LEFT
- ☐ SIDE RIGHT

☐ MOTOR/BLOWER, 1/2 HP, 2850 RPM  
(REQ'D FOR APPLICATIONS OUTSIDE NORTH AMERICA)

- ☐ EXTRA WIDTH OF UNIT
- ☐ EXTRA HEIGHT OF UNIT
- ☐ HIGHER HEADER AIR BAG
- ☐ AUTOMATIC SWITCH KIT

# 1  
# 2

S.S. QUOTE REF. # \_\_\_\_\_

CUSTOMER \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

P/O No.: \_\_\_\_\_

DATE: \_\_\_\_\_



R SERIES INFLATABLE RAIL SHELTER

4-SIDED

DATE: NOV-16-21	SCALE: N.T.S.
DRAWN: GKAX,OC,AS	DWG NO: LR-B / 2
APPROVED: RT, ST	PART NO: -