



SPRING BUMPER



DOUBLE DUTCH



1. TOP HINGE ASSEMBLY
2. BOTTOM HINGE ASSEMBLY
3. 0.064" THICK ANODIZED ALUMINUM SATIN FINISH PANELS
4. 9" WIDE x 14" HIGH CLEAR SAFETY ACRYLIC WINDOW

*** RECOMMENDED FRAMING REQUIREMENTS:
1/8" THICK x 4" WIDE FACE STEEL FRAME MOUNTED
TO A SOLID FOUNDATION.

DOOR OPENING:

_____W x _____H

- ☐ DOUBLE
☐ SINGLE – ☐ LEFT ☐ RIGHT

QUANTITY: _____

OPTIONS (CHECK BOX IF APPLICABLE)

- ☐ LAMINATE CLADDING
☐ FRONT ONLY
☐ FRONT & BACK
☐ BACK ONLY

BRAND: _____

COLOR: _____

MFR'S #: _____

- ☐ 5/16" THICK HDP SPRING BUMPERS
(HEIGHTS: 12", 21" & 42")

- ☐ CUSTOM WINDOW DESIGN
☐ RECTANGLE/SQUARE:
_____W _____H

- ☐ ROUND – DIAMETER: _____

- ☐ 9" JAMB GUARDS

- ☐ KICK PLATES

(SELECT HEIGHT)
☐ 12" ☐ 24" ☐ 36" ☐ 48"

METAL SELECTION (FRONT/BACK)

- ☐ STAINLESS STEEL/STAINLESS STEEL
☐ STAINLESS STEEL/GALV. STEEL
☐ GALV. STEEL/STAINLESS STEEL
☐ GALV. STEEL/GALV. STEEL

- ☐ CART GUARD – _____ HIGH

- ☐ CHAIN LOCKING COLLAR

- ☐ PUSH PLATE

- ☐ DOUBLE DUTCH



SERIES 1000 – MODEL SS6
DELTA EDGE ALUMINUM DOOR

DATE: OCT-02-18	SCALE: N.T.S.
DRAWN: OC, AS	DWG NO: LSS6
APPROVED: ST	PART NO: N/A

S.S. QUOTE REF. # _____
CUSTOMER _____
APPROVED BY: _____
P/O No.: _____
DATE: _____