


SPRING BUMPER



DOUBLE DUTCH

DOOR OPENING:

_____ W _____ H

QUANTITY: _____

- ☐ DOUBLE
- ☐ SINGLE
- ☐ LEFT
- ☐ RIGHT

OPTIONS (CHECK BOX IF APPLICABLE)

- ☐ 5/16" THICK HDP SPRING BUMPERS

- SELECT HEIGHT
 - ☐ 12"
 - ☐ 21"
 - ☐ 42"

- ☐ CUSTOM WINDOW DESIGN
 - ☐ RECTANGULAR/SQUARE

_____ W _____ H
☐ ROUND - DIAMETER: _____

- ☐ 9" JAMB GUARDS

- ☐ KICK PLATES
- SELECT HEIGHT
 - ☐ 24"
 - ☐ 36"
 - ☐ 48"

METAL SELECTION (FRONT/BACK)

- ☐ STAINLESS STEEL/STAINLESS STEEL
- ☐ STAINLESS STEEL/GALV. STEEL
- ☐ GALV. STEEL/STAINLESS STEEL
- ☐ GALV. STEEL/GALV. STEEL

- ☐ CART GUARD
- ☐ CHAIN LOCKING COLLAR
- ☐ DOUBLE DUTCH

1. TOP HINGE ASSEMBLY
2. BOTTOM HINGE ASSEMBLY
3. ALUMINUM COVER PANEL
4. 9" WIDE x 14" HIGH CLEAR SAFETY ACRYLIC WINDOW
5. 18 ga. STEEL KICK PLATES (SEE OPTIONS)
6. 3/4" THICK EXTERIOR GRADE PLYWOOD OUTER CORE
7. 1/2" INSULATING FOAM INNER CORE
8. GALVANIZED OR STAINLESS STEEL TRIM (TO MATCH KICK PLATE) & REPLACEABLE RUBBER GASKETING

*** RECOMMENDED FRAMING REQUIREMENTS:
1/8" THICK x 4" WIDE FACE STEEL FRAME MOUNTED
TO A SOLID FOUNDATION.



S.S. QUOTE REF. # _____
CUSTOMER _____
APPROVED BY: _____
P/O No.: _____
DATE: _____

SERIES 1000 - MODEL SS7
GASKETED & INSULATED WOOD CORE DOOR
DATE: OCT-02-18 SCALE: N.T.S.
DRAWN: OC, AS DWG NO: LSS7
APPROVED: ST PART NO: N/A