




SPRING BUMPER



KICKPLATE



PUSH PLATE



DOUBLE DITCH

DOOR OPENING: _____ W x _____ H

DOUBLE SINGLE

QUANTITY: _____

COLOR: _____

IS DOOR JAMB OVER 8"W Y N

HALLWAY INSTALLATION? Y N

OPTIONS:
(CHECK BOX IF APPLICABLE)

CUSTOM WINDOW DESIGN

RECTANGULAR _____ W x _____ H

ROUND - DIAMETER: _____

5/6" THICK HDP SPRING BUMPERS
(UP TO 42" HIGH)

1/2" HDP KICKPLATES (UP TO 48" HIGH)

1/2" HDP CART GUARD (4" HIGH)

S.S. HAND PUSH PLATE (6"W x 12"H)

9 1/4" JAMB GUARD

CHAIN LOCKING COLLAR

SLIDE LOCK

DOUBLE DITCH

- 1 - TOP HINGE ASSEMBLY (ZINC PLATED)
 - 2 - BOTTOM HINGE ASSEMBLY (ZINC PLATED)
 - 3 - ANODIZED ALUMINUM SPINE PROFILE
 - 4 - 9" WIDE x 14" HIGH CLEAR SAFETY ACRYLIC WINDOW
 - 5 - 1/2" THICK HDP DOOR BODY
- *** RECOMMENDED FRAMING REQUIREMENTS:
1/8" THICK x 4 WIDE FACE STEEL FRAME MOUNTED
TO A SOLID FOUNDATION.

S.S. QUOTE REF. # _____

CUSTOMER _____

APPROVED BY: _____

P/O No.: _____

DATE: _____



SERIES 1500 - MODEL 1501
HDP IMPACT DOOR

DATE: OCT-02-18 SCALE: N.T.S.

DRAWN: OC, AS DWG NO: L1501

APPROVED: ST PART NO: N/A