



- 1 - TOP HINGE ASSEMBLY
- 2 - BOTTOM HINGE ASSEMBLY
- 3 - ANODIZED ALUMINUM FRAME PROFILE
- 4 - 9" WIDE x 14" HIGH CLEAR SAFETY ACRYLIC WINDOW
- 5 - 1/2" THICK HDP DOOR BODY


*** RECOMMENDED FRAMING REQUIREMENTS:
1/8" THICK x 4" WIDE FACE STEEL FRAME MOUNTED
TO A SOLID FOUNDATION.




SPRING BUMPER



KICKPLATE



PUSH PLATE



DOUBLE DUTCH

DOOR OPENING:

_____ W x _____ H

☐ DOUBLE ☐ SINGLE

QUANTITY: _____

COLOR: _____

OPTIONS

(CHECK BOX IF APPLICABLE)

☐ 5/16" THICK HDP SPRING BUMPERS
(UP TO 42" HIGH)

☐ CUSTOM WINDOW DESIGN

☐ RECTANGULAR _____ W x _____ H

☐ ROUND - DIAMETER: _____

☐ 9 1/4" JAMB GUARDS

☐ KICKPLATES: (UP TO 48" HIGH)

☐ 1/2" HDP

☐ PUSH PLATES

☐ CART GUARD

☐ HDP

☐ CHAIN LOCKING COLLAR

☐ DOUBLE DUTCH

S. S. QUOTE REF. # _____

CUSTOMER _____

APPROVED BY: _____

P/O No.: _____

DATE: _____



SERIES 1500 - MODEL 1501
HDP IMPACT DOOR

DATE: NOV-21-07

SCALE: 1:24

DRAWN: OC

DWG NO: L1501