

INCREASE SAFETY AT YOUR LOADING DOCK

python
STR609

EXCLUSIVE SUPER-SEAL
"ALL WEATHER"
HOOK POSITION SENSOR
ELIMINATES LIMIT
SWITCHES & COSTLY
ADJUSTMENTS



DC GEAR MOTOR
IP-44 RATED
PROTECTS MOTOR FROM
WATER SPRAY IN ANY DIRECTION

ZINC PLATED FINISH
PROTECTS AGAINST THE
HARSHEST
WEATHER CONDITIONS

RESTRAINING FORCE OF
32,000 LBS (14,514 KGS)

ENVIRONMENTALLY-FRIENDLY,
SUSTAINABLE ALTERNATIVE
TO HYDRAULIC SYSTEMS

PYTHON STR-609 TRUCK RESTRAINT

As one of Super Seal's premium dock products, the Super Seal Truck Restraint is designed for safety and reducing the risk of dock accidents. With a high-visibility hook-style restraint arm, it is the ideal solution for keeping workers, equipment, and cargo safer during loading and unloading. Also a cost-effective alternative to hydraulic truck restraints, its rugged design makes it virtually maintenance-free with the ability to function in the toughest environments. The unique rotating hook engages over the impact guard using a restraining force of 32,000 lbs (14,514 kgs). You can rely on the dependability of this truck restraint and worry less about the direct and indirect costs of an industrial accident.

SUPER  **SEAL**

905.850.2929 - 1.800.337.3239
Fax: 905.850.2922

www.supersealmfg.com

SuperSeal Mfg. Ltd.
670 Rowntree Dairy Rd.,
Woodbridge, Ontario, Canada L4L 5T8



NEW FEATURES IN AN INDUSTRY PROVEN DESIGN

Python STR-609 Truck Restraint Standard Benefits/Features:

- **NO MECHANICAL LIMIT SWITCHES.**
Hook position constantly monitored by means of reliable, waterproof position sensor.
- **PULSE WIDTH MODULATION MOTOR CONTROL.**
Increases life of motor and mechanical parts suffer less impact damage due to integrated shock absorption.
- **RESTRAINT HOOK MAINTAINS CONTACT WITH ICC BAR**
Automatically adjusting with trailer motion.
- **INSIDE & OUTSIDE RED & GREEN L.E.D. COMMUNICATION LIGHTS.**
Providing safe, clear status of restraint position to Truck Drivers & Loading Dock Personnel.
- **EASY INSTALLATION.**
Unit mounts to dock wall above ground level.
- **LOW PROFILE.**
9" carriage, works with all standard trailers and an impact extension bar with a service range of 9" to 25".
- **DOCK LEVELER & O/H DOOR INTERLOCK CAPABILITY**
- **ZINC PLATING**
Providing all-weather durability.
- **IP-44 RATED DC GEAR MOTOR.**
Protects motor from dirt & water spray.
- **LOW POWER CONSUMPTION.**
Saving on energy costs.
- **EASY PUSH BUTTON OPERATION.**
With audible alarm override and flashing L.E.D. light
- **AVAILABLE IN ENGLISH OR FRENCH PANEL LABELING AND SIGNAGE.**
- **STATUS INDICATION LCD DISPLAY.**
Updates and system monitoring at a glance
- **ICC BAR SENSOR ALERT.**
Alerts operator if rear impact guard is NOT detected or engaged
- **STANDARD 120 VOLT (1 PHASE)**
Available in all Voltages: 220 Volt (1 phase), 230 Volt, 460 & 575 Volt (3 phase)



Combo Panel

Standard Panel

Popular Options (Not included with standard units):

- Battery Back Up (Incase Of Power Failure)
- Extension Mounting Bracket
- O/H Door Controls
- Fused Disconnect
- Dock Light Receptacle
- Inflatable Auto Interlock
- Overload For Docks
- O/D Yellow Corner/marker Lights (Red/Green L.E.D.)



Yellow Corner/Marker lights