



"U" BRACKET



VALANCE



270° HINGE

VALANCE HEIGHT

DOOR OPENING:

_____ W x _____ H

☐ - DOUBLE ☐ - SINGLE

QUANTITY: _____

COLOR: _____

OPTIONS:

(CHECK BOX IF APPLICABLE)

☐ - CUSTOM WINDOW SIZE

_____ W x _____ H

☐ - STAINLESS STEEL GRAVITY ARM

☐ - HOLD OPEN DEVICE

☐ - WIDE ANGLE 270° HINGE

☐ - EXTENSION "U" BRACKET

☐ - VALANCE _____ H

LEGEND:

1. GRAVITY ARM ASSEMBLY
2. SINGLE LAYER OF FOOD GRADE APPROVED 2.4mm THICK MONOFILAMENT PVC.
3. 13 1/2" WIDE x 13" HIGH CLEAR PVC WINDOW
4. IMPACT PLATE-DOUBLE LAYER OF MONOFILAMENT HEAT SEALED

***** RECOMMENDED FRAMING REQUIREMENTS:**

1/8" THICK X 4" WIDE FACE STEEL FRAME MOUNTED TO A SOLID FOUNDATION



SERIES 2000 - F200 LITERATURE
13"x13" WINDOW WITH OVERLAP

DATE: DEC-13-18	SCALE: 1:24
DRAWN: OC, AS	DWG NO: L2000-H / 2
APPROVED: ST	PART NO: N/A

S.S. QUOTE REF. # _____
CUSTOMER _____
APPROVED BY: _____
P/O No.: _____
DATE: _____