

INSTALLATION INSTRUCTIONS
DOCK LEVELER FILLER PADS

SUPER SEAL MFG. LTD. WILL NOT BE HELD RESPONSIBLE FOR:
IMPROPER INSTALLATION OF PRODUCT AND ITS MOUNTING COMPONENTS. INSTALLATION INTO AGED OR UNSOUND DOCK/LEVELER OR OTHER WALL OR FLOOR MATERIAL, WHICH MAY RESULT IN PREMATURE PRODUCT WEAR, PRODUCT FAILURE, PROPERTY DAMAGE, OR PERSONAL INJURY.

1. **READ INSTRUCTIONS THROUGH COMPLETELY BEFORE INSTALLATION:**
2. **MEASURE DOCK TO ENSURE PROPER DIMENSIONS:**
3. **REVIEW PARTS LIST TO ENSURE ALL PARTS HAVE BEEN SUPPLIED:**
4. **IF TOE GUARDS ARE PRESENT ON YOUR DOCK:** Remove toe guards before installing Dock Leveler Filler Pads. The removal of the toe guards on your dock will only be temporary, and can be reinstalled once Dock Leveler Filler Pads have been fully installed.
5. **DETERMINE TRIANGULAR POSITIONS OF FILLER PADS:** (Detail A)

Note: When mounting the product, make sure the Mounting Bar is facing down in towards the bottom of the dock pit. This will allow the Dock Leveler Filler Pads to fully seal the dock and will prolong the life of the product.

6. **PREPARE DOCK LEVEL FILLER PADS:** At center and 2" from each end, drill holes for 1/4" (20) x 3/4" Hex Head Screws provided, (07-0180). It is recommended to drill holes evenly spaced along each Mounting Bar. Extra mounting hardware has been included.
7. **MOUNTING TO DOCK LEVELER:** Position Dock Leveler Filler Pads on Docks side (Detail A). Make sure the Filler Pads are positioned as close to the edge of the dock as possible. Install the Filler Pads in the order shown on Detail A. Using 1/4" (20) x 3/4" Hex Head Screws provided, fasten Filler Pads to Dock. Once all Filler Pads are mounted to the dock, make sure the extra material of the Hex Head Screws, underneath the Dock, doesn't interfere with any other components.

Note: **IF UNIT HAS TOE GUARDS, GRIND THE HEX HEAD SCREWS, UNDERNEATH THE DOCK, FLUSH WITH THE DOCK. IF THE SCREWS REMAIN LONG, THEY WILL INTERFERE WITH THE TOE GUARD AND COULD RESULT IN DAMAGE TO THE EXISTING DOCK OR PERSONAL INJURY.**

PACKING LIST/DOCK

PART	QUANTITY
Assembled Filler Pads	6
1/4" x 3/4" Hex Head Tek Screws	(*) + 3

(*) – QUANTITY DEPENDS ON SIZE OF UNIT

