



- 1 - TOP HINGE ASSEMBLY
- 2 - BOTTOM HINGE ASSEMBLY
- 3 - PVC PERIMETER GASKETED EDGE TRIM (OPTIONAL)
- 4 - PREMIUM ULTRA CORE PLYWOOD CORE
- 5 - 9" x 14" CLEAR LEXAN NON-POPOUT WINDOW
- 6 - 1/8" "TUFF PLUS" ABS FACE PANEL
- 7 - CLEAR ANODIZED SPINE PROFILE

*** RECOMMENDED FRAMING REQUIREMENTS:
 1/4" THICK x 4" WIDE FACE STEEL FRAME MOUNTED
 TO A SOLID FOUNDATION.

DOOR OPENING:
 _____ W x _____ H
 DOUBLE SINGLE
 QUANTITY: _____
 COLOR: _____

OPTIONS
 (CHECK BOX IF APPLICABLE)
 GASKETED NON-GASKETED
 5/16" THICK HDP SPRING BUMPERS
 _____ H (UP TO 42" HIGH)
 CUSTOM WINDOW DESIGN (CLEAR)
 RECTANGULAR _____ W x _____ H
 ROUND - DIAMETER: _____
 9 1/4" JAMB GUARD
 KICKPLATES: (UP TO 48" HIGH)
 1/8" ABS STAINLESS STEEL
 1/2" HDP
 PUSH PLATES
 1/8" ABS STAINLESS STEEL
 CART GUARDS
 1/2" HDP
 CHAIN LOCKING COLLAR
 DOUBLE DUTCH

S. S. QUOTE REF. # _____
 CUSTOMER _____
 APPROVED BY: _____
 P/O No.: _____
 DATE: _____

SUPERSEAL

ALL-STAR SERIES - MODEL ALL-STAR 75
 LITERATURE DRAWING

DATE: JAN-31-19	SCALE: 1:24
DRAWN: OC, AC, AS	DWG NO: L-ALLSTAR / A
APPROVED: ST	PART NO: N/A