



- 1 - TOP HINGE ASSEMBLY (ZINC PLATED)
- 2 - BOTTOM HINGE ASSEMBLY (ZINC PLATED)
- 3 - ANODIZED ALUMINUM SPINE PROFILE
- 4 - 9" WIDE x 14" HIGH CLEAR SAFETY ACRYLIC WINDOW
- 5 - 1/2" THICK HDP DOOR BODY


*** RECOMMENDED FRAMING REQUIREMENTS:
1/8" THICK x 4 WIDE FACE STEEL FRAME MOUNTED
TO A SOLID FOUNDATION.



SPRING BUMPER



KICKPLATE



PUSH PLATE

DOOR OPENING:

_____W x _____H

QUANTITY: _____

COLOR: _____

IS DOOR JAMB OVER 8"W Y ☐ N ☐
HALLWAY INSTALLATION? Y ☐ N ☐

OPTIONS:
(CHECK BOX IF APPLICABLE)

☐ CUSTOM WINDOW DESIGN

☐ RECTANGULAR _____W x _____H

☐ ROUND - DIAMETER: _____

☐ 5/16" THICK HDP SPRING BUMPERS
(UP TO 42" HIGH)

☐ 1/2" HDP KICKPLATES (UP TO 48" HIGH)

☐ 1/2" HDP CART GUARD (4" HIGH)

☐ S.S. HAND PUSH PLATE (6"W x 12"H)

☐ 9 1/4" JAMB GUARD

☐ SLIDE LOCK

S. S. QUOTE REF. # _____
CUSTOMER _____
APPROVED BY: _____
P/O No.: _____
DATE: _____



SERIES 1500 - MODEL 1501-SINGLE
HDP IMPACT DOOR

DATE: NOV-17-17

SCALE: 1:24

DRAWN: OC, AS

DWG NO: L1501-A