




SPRING BUMPER



KICKPLATE



PUSH PLATE



DOUBLE DUTCH

DOOR OPENING:

\_\_\_\_\_W x \_\_\_\_\_H

DOUBLE       SINGLE

QUANTITY: \_\_\_\_\_

COLOR: \_\_\_\_\_

OPTIONS:

(CHECK BOX IF APPLICABLE)

- CUSTOM WINDOW DESIGN
  - RECTANGULAR \_\_\_\_\_W x \_\_\_\_\_H
  - ROUND - DIAMETER: \_\_\_\_\_
- 5/16" THICK HDP SPRING BUMPERS (UP TO 42" HIGH)
- KICKPLATES (UP TO 48" HIGH)
  - 1/4" ABS
- CART GUARD (4" HIGH)
  - 1/4" ABS
- 9 1/4" JAMB GUARD
- CHAIN LOCKING COLLAR
- DOUBLE DUTCH
- S.S. HAND PUSH PLATE (6"W x 12"H)

- 1 - TOP HINGE ASSEMBLY (ZINC PLATED)
- 2 - BOTTOM HINGE ASSEMBLY (ZINC PLATED)
- 3 - ANODIZED ALUMINUM SPINE PROFILE
- 4 - 9" WIDE x 14" HIGH CLEAR SAFETY ACRYLIC WINDOW
- 5 - 1/2" THICK CHEMICALLY BONDED ABS DOOR BODY
- 6 - FULL PERIMETER GASKETTING

\*\*\* RECOMMENDED FRAMING REQUIREMENTS:  
 1/8" THICK x 4" WIDE FACE STEEL FRAME MOUNTED  
 TO A SOLID FOUNDATION.

S.S. QUOTE REF. # \_\_\_\_\_

CUSTOMER \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

P/O No.: \_\_\_\_\_

DATE: \_\_\_\_\_



SERIES 1500 - MODEL 1505  
 ABS FULLY GASKETED IMPACT DOOR

DATE: OCT-02-18	SCALE: N.T.S.
DRAWN: OC, AS	DWG NO: L1505
APPROVED: ST	PART NO: N/A