



1. TOP HINGE ASSEMBLY
2. BOTTOM HINGE ASSEMBLY
3. HIGH PRESSURE LAMINATE CLAD
4. 9" WIDE x 14" HIGH CLEAR SAFETY ACRYLIC WINDOW
5. 3/4" THICK EXTERIOR GRADE PLYWOOD CORE
6. 18 ga. STEEL KICK PLATES (SEE OPTIONS)
7. GALVANIZED OR STAINLESS STEEL TRIM


*** RECOMMENDED FRAMING REQUIREMENTS:
 1/8" THICK x 4" WIDE FACE STEEL FRAME MOUNTED
 TO A SOLID FOUNDATION.



GASKETED



SPRING BUMPER



DOUBLE DUTCH

DOOR OPENING:
 _____ W _____ H

QUANTITY: _____

DOUBLE
 SINGLE
 LEFT
 RIGHT

LAMINATE CLADDING
 BRAND: _____
 COLOR: _____
 MFR'S #: _____

KICK PLATES
 SELECT HEIGHT
 18"
 24"
 36"
 FULL HEIGHT
 METAL SELECTION (FRONT/BACK)
 STAINLESS STEEL/STAINLESS STEEL
 STAINLESS STEEL/GALV. STEEL
 GALV. STEEL/STAINLESS STEEL
 GALV. STEEL/GALV. STEEL

OPTIONS (CHECK BOX IF APPLICABLE)

GASKETED

5/16" THICK HDP SPRING BUMPERS
 (KICKPLATE REMAINS BEHIND BUMPER)
 SELECT HEIGHT
 12"
 21"
 42"

CUSTOM WINDOW DESIGN
 RECTANGULAR/SQUARE
 _____ W _____ H
 ROUND - DIAMETER: _____

9" JAMB GUARDS
 CART GUARD
 CHAIN LOCKING COLLAR
 DOUBLE DUTCH

S.S. QUOTE REF. # _____
 CUSTOMER _____
 APPROVED BY: _____
 P/O No.: _____
 DATE: _____



SUPER SEAL

SERIES 1000 - MODEL SS4
 NON-GASKETED WOOD CORE DOOR

DATE: OCT-02-18	SCALE: N.T.S.
DRAWN: OC, AS	DWG NO: LSS4
APPROVED: ST	PART NO: N/A